



PROJOINT

NATURAL BRASS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROJOINT is a natural brass joint for joining two floors laid with mortar or glue/adhesive. The head thickness allows perfect smoothing and sanding of over 3 mm. It is usually used for tile-wood-marble-Venetian-Palladian floors. Available in various heights and widths. The vertical arrowhead part in the PIT 510 and PIT 514 glue version allows excellent anchorage with the adhesive.



POLISHABLE NATURAL BRASS thermo packed 10 Pcs

bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	L x H mm		
PITON 1025	10 X 25		
PITON 525	5 X 25		
PITON 514	5 X 14		
PITON 510	5 X 10		



POLISHABLE NATURAL BRASS

bar length 0,90 lm - pack 40 Pcs

Article	L x H mm		
PITON 5109	5 X 10		

CONSISTING OF 1 ECOBLISTER WITH 2 PCS. OF 0.90 LM




COLOURS


ON	ON DEMAND
ON - Natural brass	OL - Polished brass

PROJOINT

NATURAL ALUMINIUM



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROJOINT is a natural aluminium joint for joining two floors laid with mortar or glue/adhesive. The head thickness allows perfect smoothing and sanding of over 3 mm. It is usually used for tile-wood-marble-Venetian-Palladian floors. Available in various heights and widths. The vertical arrowhead part in the PIT 510 and PIT 514 glue version allows excellent anchorage with the adhesive.



NATURAL ALUMINIUM thermo packed 10 Pcs

bar length 2,70 lm - pack 40 Pcs - 108 lm

Article	L x H mm		
PITAN 525	5 X 25		
PITAN 514	5 X 14		
PITAN 510	5 X 10		

COLOURS

AN
AN - Natural alum.