




**PROCANAL** is a channel for joining floors and also for use as strips in wall coverings. This profile is made in natural, polished and chromed brass as well as natural or anodised silver aluminium. It is also used as a cable channel for the insertion of wires and conduits in all types of floor.

## PROCANAL

NATURAL, POLISHED AND CHROMED BRASS  
NATURAL AND ANODISED SILVER ALUMINIUM



**NATURAL BRASS thermo packed 10 Pcs**  
**POLISHED and CHROMED BRASS thermo packed**  
bar length 2,7 lm - pack 40 Pcs - 108 lm (PCLOC 10 - 81 lm)

Article	L x H mm
PCLON 10 (natural)	10 X 10
PCLOL 10 (polished)	10 X 10
PCLOC 10 (chromed)	10 X 10

Available Stainless steel AISI 304/1.4301-V2A  
"PROLISTEL" 10x10 PLTAC 10 / PLTACS 10 (page 36)


### COLOURS




**NATURAL ALUMINIUM thermo packed 10 Pcs**  
**ANODISED SILVER ALUMINIUM thermo packed**  
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	L x H mm
PCLAN 10 (natural)	10 X 10
PCLAA 10 (anodised silver)	10 X 10

PCL... 10



### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile in the required material and finish. 2. Apply the adhesive onto the area of application. 3. Lay the "PROCANAL". 4. Continue laying by aligning it "flush" with the covering. 5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

**PROFLAT** is a range of 20 and 40 mm natural brass or steel strips 3 mm thick. Ideal for dividing up flooring on the same level, they may be polished in situ and also curved/shaped to create decorative patterns that are particularly recommended for marble, Palladian, Venetian and cement or resin-based floors.

## PROFLAT

STAINLESS STEEL AISI 304/1.4301-V2A  
NATURAL BRASS



**STAINLESS STEEL AISI 304/1.4301-V2A**  
bar length 3 lm - pack 5 Pcs - 15 lm

Article	L x H mm
GPLAC 2033	3 X 20
GPLAC 4033	3 X 40

**STAINLESS STEEL AISI 304/1.4301-V2A**  
bar length 3 lm - pack 5 Pcs - 15 lm

Article	L x H mm
GPLAC 2053	5 X 20
GPLAC 5053	5 X 50

Available ON REQUEST IN SATINED Stainless steel  
SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.




**POLISHABLE NATURAL BRASS**  
bar length 2,7 lm - pack 5 Pcs - 13,5 lm

Article	L x H mm
GPLON 2025	2,5 X 20
GPLON 4025	2,5 X 40


### COLOURS




GPLAC 203... / 205...



GPLON 2025




GPLAC 403... / 505...



GPLON 4025



### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROFLAT" with the same height as the thickness of the floor. 2. Cut the profile to the necessary length and place it along the edge of the laid floor or insert it from above. 3. Continue the laying "flush" with the "PROFLAT".

\* = On demand, price and delivery time to be agreed.